DEA-Solver-Pro Newsletter

No. 6
(May 1, 2006)

We announce that Version 5.0 is now on the market as the successor of Version 4.1 of DEA-Solver-Pro.

In this new Version 5.0, we reinforced our collection of DEA models by the addition of Hybrid model and the Weighted SBM model, and modified the Non-separable Outputs model in the Undesirable Outputs cluster. We also added worksheets “Decomposition” to the SBM-family and Non-separable Output models. This includes the decomposition of efficiency score into inefficiency of each input/output factor.

The Hybrid model deals with radial and non-radial inputs/outputs in a unified framework. The Weighted SBM model puts weights to slacks in accordance with their importance to management.

In Version 4.1, we enriched our collection of DEA models by the addition of Undesirable Outputs models. In accordance with the global environmental conservation awareness, undesirable outputs of production and social activities, e.g., air pollutants and hazardous waste, have been widely recognized as societal evils. Thus, development of technologies with less undesirable outputs is an important subject of concern in every area of production. DEA usually assumes that producing more outputs relative to less input resources is a criterion of efficiency. In the presence of undesirable outputs, however, technologies with more good (desirable) outputs and less bad (undesirable) outputs relative to less input resources should be recognized as efficient. The Undesirable Model deals with this problem. Please see Newsletter 5.

All DEA models can be classified into three types: (1) Radial, (2)

Non-Radial and Oriented, and (3) Non-Radial and Non-Oriented. 'Radial' means that a proportionate change of input/output values is the main concern and hence it neglects the existence of slacks (input excesses and output shortfalls remaining in the model) as secondary or freely disposable, whereas 'Non-Radial' deals with slacks directly and does not stick to a proportionate change of input/output. 'Oriented' indicates the input or output orientation in evaluating efficiency, i.e., the main target of evaluation is either input reduction or output expansion. For example, input oriented models first aim to reduce input resources to the efficient frontier as far as possible, and then to enlarge output products as the second objective. 'Non-Oriented' models deal with input reduction and output expansion at the same time.

Version 5.0 consists of 145 models in 35 clusters. They are classified into the three categories as displayed below.

Category	Cluster or Model
Radial	CCR, BCC, IRS, DRS, AR, ARG, NCN, NDSC, BND, CAT, SYS, Bilateral, Scale Elasticity, Congestion, Window, Malmquist-Radial, Adjusted Projection, FDH
Non-Radial and Oriented	SBM-Oriented, Super-efficiency-Oriented, Malmquist
Non-Radial and Non-Oriented	Cost, New-Cost, Revenue, New-Revenue, Profit, New-Profit, Ratio, SBM-NonOriented, Super-SBM-NonOriented, Malmquist-C (V, GRS), Undesirable Outputs, Weighted SBM
Radial and Non-Radial	Hybrid

The following 145 models in 35 clusters are included. (Red marks are newcomers since Version 4.0.)

No.	Cluster	Model
1	CCR	CCR-I, CCR－O
2	BCC	BCC-I, BCC-O
3	IRS	IRS-I, IRS-O
4	DRS	DRS-I, DRS-O
5	GRS	GRS-I, GRS-O
6	AR (assurance region)	AR-I-C, AR-I-V, AR-I-GRS, AR-O-C, AR-O-V,

		AR-O-GRS
7	ARG (assurance region global)	ARG-I-C, ARG-I-V, ARG-I-GRS, ARG-O-C, ARG-O-V, ARG-O-GRS
8	NCN (non-controllable)	NCN-I-C, NCN-I-V, NCN-O-C, NCN-O-V
9	NDSC (non-discretionary)	NDSC-I-C, NDSC-I-V, NDSC-I-GRS, NDSC-O-C, NDSC-O-V, NDSC-O-GRS
10	BND (bounded variable)	BND-I-C, BND-I-V, BND-I-GRS, BND-O-C, BND-O-V, BND-O-GRS
11	CAT (categorical variable)	CAT-I-C, CAT-I-V, CAT-O-C, CAT-O-V
12	SYS (different systems)	SYS-I-C, SYS-I-V, SYS-O-C, SYS-O-V
13	SBM-Oriented (Slacks-based Measure)	SBM-I-C, SBM-I-V, SBM-I-GRS, SBM-O-C, SBM-O-V, SBM-O-GRS, SBM-AR-I-C, SBM-AR-I-V, SBM-AR-O-C, SBM-AR-O-V
14	SBM-Non Oriented	SBM-C, SBM-V, SBM-GRS, SBM-AR-C, SBM-AR-V
15	Weighted SBM	WeightedSBM-C, WeightedSBM-V, WeightedSBM-I-C, WeightedSBM-I-V, WeightedSBM-O-C, WeightedSBM-O-V
16	Super-SBM-Oriented	Super-SBM-I-C, Super-SBM-I-V, Super-SBM-I-GRS, Super-SBM-O-C, Super-SBM-O-V, Super-SBM-O-GRS
17	Super-SBM-NonOriented	Super-SBM-C, Super-SBM-V, Super-SBM-GRS
18	Super-Radial	Super-CCR-I, Super-CCR-O, Super-BCC-I, Super-BCC-O
19	Cost	Cost-C, Cost-V, Cost-GRS
20	New-Cost	New-Cost-C, New-Cost-V, New-Cost-GRS
21	Revenue	Revenue-C, Revenue-V, Revenue-GRS
22	New-Revenue	New-Revenue-C, New-Revenue-V, New-Revenue-GRS
23	Profit	Profit-C, Profit-V, Profit-GRS
24	New-Profit	New-Profit-C, New-Profit-V, New-Profit-GRS
25	Ratio (Revenue/Cost)	Ratio-C, Ratio-V
26	Bilateral	Bilateral
27	Window	Window-I-C, Window-I-V, Window-I-GRS, Window-O-C, Window-O-V, Window-O-GRS
28	FDH	FDH
29	Adjusted Projection	Adj-CCR-I, Adj-CCR-O, Adj-BCC-I, Adj-BCC-O, Adj-AR-I-C, Adj-AR-I-V, Adj-AR-O-C, Adj-AR-O-V
30	Malmquist-NonRadial	Malmquist-I-C, Malmquist-I-V, Malmquist-I-GRS, Malmquist-O-C, Malmquist-O-V, Malmquist-O-GRS, Malmquist-C, Malmquist-V, Malmquist-GRS
31	Malmquist-Radial	Malmquist-Radial-I-C, Malmquist-Radial-I-V, Malmquist-Radial-I-GRS, Malmquist-Radial-O-C, Malmquist-Radial-O-V, Malmquist-Radial-O-GRS
32	Scale Elasticity	Elasticity-I, Elasticity-O
33	Congestion	Congestion
34	Undesirable outputs	BadOutput-C, BadOutput-V, BadOutput-GRS, NonSeparable-C, NonSeparable-V, NonSeparable-GRS
35	Hybrid	Hybrid-C, Hybrid-V, Hybrid-I-C, Hybrid-I-V, Hybrid-O-C, Hybrid-O-V

The meanings of the extensions -C, -V and –GRS are as follows. Every DEA model assumes a returns to scale (RTS) characteristics that is represneted by the range (L, U) of the sum of the intensity vector λ. The constant RTS (-C) corresponds to (L=0, U=infinity) and the variable RTS (-V) to (L=1, U=1), respectively. In the models with the extension GRS, you have to supply L and U from keyboard, the defaults being L=0.8 and U=1.2. The increasing RTS (IRS) corresponds to (L=1, U=infinity) and the decreasing RTS (DRS) to (L=0, U=1), respectively. It is recommended to try several sets of (L, U) in order to identify how the RTS chracteristics exerts an influence on the efficiency score.